

YANTON®

Type-C charging port



YANTON W7 Earphone POC Walkie Talkie

- Support 4G/ LTE/3G/2G network
- Support Group Call, Single Call , Friendly Call, Emergency Call
- Bluetooth Function (optional)
- Mini Design
- Linux System



TECHNIQUE SPECIFICATION

General	Dimensions (H*W*D)	68mm*32mm*17mm
	Weight(Includes battery)	≈ 37G
	Working temperature	-30℃~+75℃
	Operating Voltage	DC3.3V-4.2V(Recommended value 3.8V)
	Working current	Peak current ≈ 0.6A
	Average current	≈ 540mA@UMTS2100: ≈ 239mA@GSM900
	Stand-by current	≈ 5mA@UMTS: ≈ 5mA@GSM
	Battery Capacity	800mAh
	Charger mode	Type-c
Baseband	(U) SIM/SIMU	Standard SIM Card Slot: Support 3VSIM Card and 1.8VSIM Card
	UART Connector	8 pins UART
	Maximum power consumption	≈ 2.2uw
	UMTS Frequency Band	HSDPA/WCDMA: B1/2/3/4/5/7/8/20/28/34/38/39/40/41 B1/2/3/4/5/7/8/12/13/17/34/38/39/40/41
Frequency	TX Power	UMTS2100/1900/900/850:power level 3(+24dBm+2.5/-1.5dBm)
		EDGE850MHz/900MHz:power level E2(+27dBm+4.5/-1.5dBm)
		EDGE1800MHz/1900MHz:power level E2(+26dBm+4.5/-2.5dBm)
		WCDMA2100: ≤ -108dBm
	RX Sensitivity	WCDMA1900: ≤ -109dBm
		WCDMA900: ≤ -109dBm
		WCDMA850: ≤ -109dBm
		GSM850/900/1800/1900: ≤ -107dBm

PACKING LIST



QUANZHOU YANTON ELECTRONICS CO.,LTD

<http://www.yantonradio.com>